

## IN THE CLAIMS

1 (Currently Amended). A cellular telephone comprising:  
an applications processor;  
a baseband processor;  
a first bus coupling said processors; and  
a device to ~~detect an attempt to make an emergency call and~~ to selectively bypass the applications processor if the applications processor fails to respond within a time period, ~~after said attempt~~, by diverting signals from the applications processor to the baseband processor.

Claim 2 (Canceled).

3 (Previously Presented). The telephone of claim 1 including a keypad, said applications processor coupled to said keypad to receive keypad inputs.

4 (Previously Presented). The telephone of claim 1 including a display, said applications processor coupled to said display to provide outputs to said display.

Claims 5-7 (Canceled).

8 (Previously Presented). The telephone of claim 1 wherein said telephone includes a keypad, keypad entries being provided to said applications processor, said device selectively shunting said keypad entries to said baseband processor.

9 (Previously Presented). The telephone of claim 1 including a display, said display coupled to receive outputs from said applications processor, said device to selectively bypass the applications processor to provide outputs to said display from said baseband processor.

10 (Previously Presented). The telephone of claim 1 including a display and a keypad, said applications processor coupled to said display and said keypad and said baseband processor coupled to said display and said keypad through said applications processor and said device.

11 (Currently Amended). A method comprising:  
establishing communications between an input/output device and a first processor,  
that acts as an applications processor, to execute a first task; and  
in response to the detection of an attempt to make an emergency call and a failure  
of the first processor to respond to said attempt within a period of time, providing said  
communications to a second processor so that the second processor executes the first task in place  
of the first processor.

12 (Original). The method of claim 11 including selectively coupling keypad entries to a  
second processor when a first processor fails to respond.

13 (Original). The method of claim 11 including coupling keypad entries directly to the  
first processor except when the first processor fails to respond.

14 (Original). The method of claim 11 including detecting an emergency call and in  
response to the detection of an emergency call, coupling keypad entries directly to a baseband  
processor.

15 (Original). The method of claim 11 wherein detecting an event includes detecting the  
failure of a first processor to respond.

16 (Original). The method of claim 15 including detecting the failure of the first processor  
to respond within a predetermined amount of time.

17 (Original). The method of claim 11 including coupling said second processor to said  
first processor and coupling said first processor directly to a keypad and a display.

18 (Original). The method of claim 17 including selectively coupling said display and said  
keypad directly to said second processor.

Claim 19 (Canceled).

20 (Previously Presented). The method of claim 11 including providing a second processor that acts as a baseband processor.

Claims 21-30 (Canceled).

31 (New). The telephone of the telephone of claim 1 wherein said device to detect an attempt to make an emergency call and in such case and, only in such case, selectively bypass the applications processor when the applications processor fails to respond within a time period after the attempt.

32 (New). The method of claim 11 including detecting an attempt to make an emergency call and in such case and, only in such case, selectively bypass the applications processor when the applications processor fails to respond within a time period after the attempt.